At your side.

brother®

MFC-9180

MFC-9180

Flexible and efficient business communication.

- Laser Copier
- Laser Printer
- Laser Fax
- Colour Scanner

09/06 15:25 FAX
Back-lit Display

up to 10 ppm
Up to 10ppm

Parallel/USB

PCL® 5e
PCL®5e

8 MB
8MB Memory

up to x30 ADF
Up to 30 page ADF

14.4k bps
Fax Facility

At your side.

brother

MFC

A professional and highly versatile communication

MFC-9180

The Brother MFC-9180 encompasses a Laser Copier, Laser Printer, Laser Fax and Colour Scanner. This Digital Multi-Function Centre is designed to meet the needs of business professionals whether at home or at work. And because it's from Brother, you can rest assured that it delivers outstanding and efficient performance across all functions.

-9180

solution

Features

Laser Copier

Performance copying

The MFC-9180 copier function produces high quality copies. The machine's flexible and reliable features – which includes stack or sort functions as well as a zoom range of 25% to 400% – delivers superb results.

Key Features:

- Flatbed Design
- Back-lit Display
- Up to 200 Sheet Paper Capacity
- Up to 30 Sheet ADF
- Stack or Sort Functions
- 25% - 400% Reduction/Enlargement in 1% Increments
- 2 in 1, 4 in 1 Reduction, Poster enlargement

Laser Printer

Fast printing of the highest quality

With a Windows® printing speed of up to 10 pages per minute and up to 600 x 600 dpi resolution, the MFC-9180 combines speed and quality output perfectly. The printing function is flexible and efficient, and the MFC-9180 is designed to support Windows®95 and 98, Me, Win NT®4.0, 2000 Professional and MacOS™ 8.5-9.1.

Key Features:

- Up to 10 ppm
- Up to 600 x 600 dpi Print Resolution
- Parallel and USB Interfaces
- PCL®5e Emulation

Laser Fax

Better communication, easier management

The MFC-9180 fax function offers professional faxing with a 14.4 Kbps Fax modem, 100 pre-set numbers and a dual access facility allowing the machine to prepare faxes to be sent whilst you are already sending or receiving a message.

Key Features:

- 14.4 Kbps Fax Modem
- Up to 400 page receive or transmit memory**
- MH, MR, MMR Compression
- Dual Access Memory
- Navigation Key
- 100 Speed Dials
- Broadcasting
- Group Dial
- Memory Security

Colour Scanner

From paper to digital

Converting information is fast and easy with the MFC-9180 scanning system. Colour scanning capabilities and a scan to e-mail facility ensure flexible and professional results.

Key Features:

- Scan from bound documents or automatic document feeder
- Up to 9600 x 9600 dpi Resolution (interpolated)
- 24 bit Colour Depth
- Scan to e-mail*
- Scan to OCR*
- Scan to File
- Twain Compliant

*For Windows® only

**Based upon ITU-T Test Chart No 1

MFC-9180

MFC-9180

Technical Specification

Toner & Drum

General

Engine	Laser
Modem Speed (bps)	14,400, 9,600, 7,200, 4,800, 2,400
Transmission Speed	Approx 6 seconds (Brother Test Chart No 1 MMR)
ITU-T group compatibility	G3
Data Compression	MH / MR / MMR
Input / Output Width	Up to 216mm
ADF (Auto Document Feed)	Up to 30 sheets
LCD Display Size	2 lines of 16 characters with Back-lit Display
On-Screen Programming	Step by step prompts are displayed within the LCD in order to facilitate programming machine options and settings.
CPU Speed	RISC-100MHz
Back-up for clock	Up to 9 hrs
Total Memory Capacity	8 MB (RAM)
Memory Back-up	Up to 4 days
Memory Security / Transmission Lock	Allows prevention of unauthorised access to the fax machine.
Simultaneous Operation	(Print / Fax), (Print / Copy), (Print / Scan)
Paper Capacity	Up to 200 sheets
Output Paper Capacity	Up to 50 sheets
Paper Handling Size	Maximum A4

Printer

Speed	Up to 10 pages per minute in Windows
Resolution	Up to 600 x 600 dpi
Standard Print Language	Windows GDI
Emulation	PCL5e

Fax

Automatic Redial	Automatic redialling if the recipient fax is busy
Speed Dial Locations	100 Speed Dial locations
Group Dial	Up to 6 groups
FAX/TEL Switch	Automatic recognition of fax and telephone reception
Super Fine	Enables quality transmission of very small print and line drawings
Grey Scale	64 levels
Contrast	Auto / light / dark
Enhanced Remote Activation	Transfer a fax call, answered at an extension phone, to the fax machine
Delayed Timer	Up to 50
Polling Type	Standard, Secure, Delayed and Sequential
Quick-Scan	Reduce scanning times by scanning a fax into memory before sending. Approximately 2.8 seconds per A4 standard
Page Memory	Up to 400 pages (MMR / Standard Resolution) ITU-T Chart No 1
Dual Access	Allows the operator to perform 2 different tasks on the machine at the same time
Broadcasting	Send the same fax message to up to 150 separate locations (manual 50 locations)
Batch Transmission	Stores documents for the same location in the machines memory for transmission in a single call.
Auto Reduction	When receiving a single page document between 297mm and 350mm long the fax will automatically reduce the message to fit onto a single A4 sheet
ECM (Error Correction Mode)	Where machines share the same ECM feature, detects errors during fax transmission
Fax Forwarding	Sends a fax received in memory to another pre-programmed fax number
Remote Retrieval	Allows you to call your machine from any touch tone phone or group 3 fax set for tone and retrieve a fax.
PC Fax	Faxes can be transmitted directly from a PC (send only) no RX

Copier

Speed	Up to 10 copies per minute
Resolution	Up to 600 x 300 dpi
Multi-Copying / Stack / Sort	Makes up to 99 copies of each page loaded in the ADF / Stacks or Sorts
Enlargement / Reduction Ratio	Reduce or Increase document sizes from 25% to 400% in 1% increments or 6 pre-set ratios
2 in 1 / 4 in 1 Copy	Allows the user to compress 2 or 4 pages onto a single A4 sheet

Scanner

Resolution (Optical)	Up to 600 x 2,400 dpi
Resolution (Interpolated)	Up to 9,600 x 9,600 dpi
Grey Scale	256 shades of grey available for copying, faxing or scanning
PCI Scanner (Parallel / USB)	The MFC-9180 has Parallel and USB connections
Scan to Key	Scan to E-mail, Scan to File, Scan to OCR*

List / Report

Journal Report	Lists information about the last 200 incoming and outgoing faxes.
TX (Transmission) Verification Report	Reports transmission details after each fax is sent.
Cover-page	Generates a cover page at the recipients machine.
Help List	By pressing the report key a list of basic operational steps and functions can be printed

Interface

External TAD Interface	Interface for connecting external telephone answering devices
Host Interface (IEEE1284)	Parallel cable port
Host Interface (USB)	USB (Universal Serial Bus) cable port

Weights and Measures

Dimensions	459mm width x 458mm depth x 354mm high
Weight	11 Kg
Power Consumption	Sleep: 15 w or less Stand-by: 75 w or less Peak: 940 w or less

Consumables

Toner	TN-8000 (Approx 2,200 pages with 5% coverage)
Drum	DR-8000 (Up to 8,000 pages @ 5% coverage with 1 page per job)

Operating Systems

	Microsoft® Windows®	PC Fax Send	Twain Driver	Printer Driver	Brother Control Centre	Remote Setup	ScanSoft™ PaperPort®
MFC-9180	95	✔	✔	✔	✔	✔	✔
	98/98SE	✔	✔	✔	✔	✔	✔
	Me	✔	✔	✔	✔	✔	✔
	NT®4.0 WS	✔	✔	✔	✔	✔	✔
	2000 Professional	✔	✔	✔	✔	✔	✔
	Macintosh®	**PC Fax Send**	**Twain Driver**	**Printer Driver**	**Brother Control Centre**	**Remote Setup**	**ScanSoft™ PaperPort®**
	OS 8.5.1	✔	✘	✔	✘	✘	✘
	OS 8.6	✔	✔	✔	✘	✘	✘
	OS 9.0 / 9.0.4	✔	✔	✔	✘	✘	✘
	OS 9.1	✔	✔	✔	✘	✘	✘

For Windows XP and Mac OSX compatibility please visit the solutions centre website at http://solutions.brother.com

*For Windows® only

Contact:

At your side.

Brother UK Ltd.,
Audenshaw, Manchester M34 5JD
Tel: +44 (0)161-931 2354 Fax: +44 (0)161-931 2204
Web-site: www.brother.co.uk

Your calls to us may be monitored or recorded for training purposes.
Specification correct at time of going to print. Brother is a registered trademark of Brother Industries Ltd.
Brand product names are registered trademarks of their respective companies.

ZLFTMFC9180U1 11/2001 Fi